

UVSS

United Vision Security Solutions
Long Range IR Night-Vision Camera Systems

FST. 2000



UVSS

FST. 2000

EV3000

**Off-Shore/Harbor/Border/Marine/Navy
Long Range Camera System**



UVSS

EST. 2000

EV3000 Models D-IR 100-100H

Eagle Vision Dual Sensors

IR Thermal / Color Cameras

- All Weather Rugged Housing resists high humidity, salt water, and rust
- Special cooling system to reduce heat by 15° C
- 128 preset positions for perimeter scanning
- Pelco-D protocols that can be integrated with any other pre-existing CCTV system or Radar.
- Enviromentally sealed
- Image overlay combines thermal and video image
- The EV3000 CCD or EMCCD color night vision camera provides high resolution full color images from full sunlight down to quarter moonlight, and thereafter monochrome images down to starlight.

IR Thermal Imager

- 640x480 or 320x240 Detector
- Un-cooled 7-14 Micron
- Auto-Focus
- 100mm Lenses
- Digital Detail Enhancement (DDE)

Sensor Platform

- Heavy Duty, Stabilized Pan/Tilt
- Rugged housing for marine applications
- This product can be used in any marine applications and harsh enviroments
- Inclues Anti-Rust and Anti-Corrosion with full sealed housing and Pan-Tilt
- Great for shores, sea ports or ships

Day/Night Camera



- 1/2" (1.27 cm) High-Resolution CCD or EMCCD
- 0.03 lx / 0.000008 lx (Sensup on)
- Lens 12-660/30-1680mm - 55x Optical Zoom
- Reproduces full color, full motion images in fog and low light

Pan/Tilt Resolution

- High performance, brushless, maintenance-free step motors provide very precise and extremely effective motion control with presets and full 360° endless rotation

Options

- Digital Real-Time Video Stabilization
- TCP/IP Interface
- Washer and Wiper



UVSS

EST. 2000

EV3000 Model D-IR 100

Eagle Vision Dual Sensors

Model Specifications

EV3000-D-IR100

Thermal Resolution

320 x 240

IR Focal Lenses

100mm

Day Lenses

10-330mm

Detection Range

1-4 km (~0.6-2.5 mi)

Day/Low Light



Dark/Fog/Smoke



Man: 1.8 m x 0.5 m



Detection approx. 1.6 km



Recognition approx. 400 m



Identification approx. 200 m

Object: 2.3 m x 2.3 m



Detection approx. 4.4 km



Recognition approx. 1.1 km



Identification approx. 580 m

UVSS

EST. 2000

EV3000 Model D-IR 100 H

Eagle Vision Dual Sensors

Model Specifications

EV3000-D-IR100 H

Thermal Resolution

640 x 480

IR Focal Lenses

100mm

Day Lenses

10-330mm

Detection Range

3-6 km (~1.9-3.7 mi)

Day/Low Light



Dark/Fog/Smoke



Man: 1.8 m x 0.5 m



Detection approx. 1950 m



Recognition approx. 510 m



Identification approx. 260 m

Object: 2.3 m x 2.3 m



Detection approx. 5000 m



Recognition approx. 1400 m



Identification approx. 720 m

UVSS

EST. 2000

EV3000

Model D-IR-100, D-IR-100H

Eagle Vision Dual Sensors

FEATURES		EV3000-D-IR-100	EV3000-D-IR-100H
Thermal Imaging	Detector type	Focal Plane Array/ uncooled microbolometer	Focal Plane Array/ uncooled microbolometer
	Pixel Count (Resolution)	324 X 256	644 X 512
	Spectral Response	7.5 to 13 μ m	
	Image processing	Automatic Gain Control (AGC), Digital Detail Enhancement (DDE)	
	FOV (H X V) Digital Zoom Focal Length (mm)	7° (H) x 5° (V) 2X, 4X (100H model) 100 mm	
Video	Sensor	1/2 inch CCD High sensitivity color / monochrome camera or 1/2 inch EMCCD	
	Field of View	40.84° to 0.69° (12-660mm) 15.12° to 0.27° (30-1580mm)	
	Zoom	Optical: 55X 12-660mm/30-1680mm with 2.5 extender	
	Illumination	0.000008 lx with setup	
Pan & Tilt	Azimuth Control	360° continuous	
	Elevation Control	-90 ° +45 °	
	Pan & Tilt Slew Rate	0 seconds to 60 seconds	
	Pointing Accuracy	Pan \pm 0.1° / Tilt \pm 0.1°	
Power	Power Source	10 - 28 VDC through supplied 110 /220 VAC power supply	
Environmental Characteristics	Operating Temperature	-40° C to 60° C	
	Environmental Sealing	Fully ruggedized IP66	

Thermal / Color Cameras

- **All Stainless Steel, Rugged Housing**
 - Anti-Corrosion, Anti Rust, High humidity and salt water resistant.
- **Special cooling system to reduce heat by 15° C**
- **128 preset positions for perimeter scanning with a tour function**
- **Pelco-D protocols that can be integrated with any other pre-existing CCTV system.**
- **Environmentally sealed**
- **Image overlay combines thermal and video image**
- **The EV3000 CCD or EMCCD color night vision camera provides high resolution full color images from full sunlight down to quarter moonlight, and thereafter monochrome images down to starlight.**



Thermal Imager

- 640 x 480
- Un-cooled 7-14 Micron
- DFOV, Zoom, Digital Zoom,
- 50/250mm Lens

Day/Night Camera

- 1/2" (1.27 cm) High-Resolution EMCCD
- Min. Illumination < 200µlux
- Lens 16.7mm-1000/33
 - 2000mm Optical Zoom
- Reproduces full color, full motion images in fog and low light, and starlight conditions

CCTV with TCP/IP

- Full control of Thermal, Day-Night, Pan/Tilt using Standard Protocol Pelco-D

Sensor Platform

- Heavy Duty, Stabilized Pan/Tilt
- Stainless Steel Enclosure
- This product can be used in any marine applications and harsh environments
- Includes Anti-Rust and Anti-Corrosion with full sealed housing and Pan-Tilt
- Great for shores, sea ports or ships

Pan/Tilt Resolution

- High performance, brushless, maintenance-free step motors provide very precise and extremely effective motion control with presets and full 360° endless rotation

Options

- Digital Real-Time Video Stabilization
- Washer and Wiper
 - 5 or 10 ITR

UVSS

EST. 2000

EV3000 Model D-IR 250

Eagle Vision Dual Sensors

Model Specifications

EV3000-D-IR250

Thermal Resolution

640 x 480

IR Focal Lenses

50/250mm

Day Lenses

10-550mm

Detection Range

3-6 km (~1.9-3.7 mi)

Day/Low Light ✓

Dark/Fog/Smoke ✓

Man: 1.8 m x 0.5 m



Detection approx. 10 km




Recognition approx. 3.5 km



Identification approx. 2km

Object: 2.3 m x 2.3 m



Recognition approx. 8 km



Identification approx. 4 km

Detection approx.

21 km

UVSS

EST. 2000

EV3000

Model D-IR-100, D-IR-250

Eagle Vision Dual Sensor

FEATURES		EV3000-D-IR-100	EV3000-D-IR-250
Thermal Imaging	Detector type	Focal Plane Array/ uncooled microbolometer	Indium Antimonide (InSb); 640x480 detector ,
	Pixel Count (Resolution)	320 X 240, 25µm micron pitch	15µm micron pitch, high-resolution has 4-times the picture clarity of cameras that use medium format 320x240
	Spectral Response	7.5 to 13 µm	3 - 5 µm
	Image processing	Automatic Gain Control (AGC), Digital Detail Enhancement (DDE)	Digital Detail Enhancement (DDE) On/Standby/Off, Auto & manual Level, manual Gain, Polarity, reticle on/off/select, Non-Uniformity Correction, Change FOV, Focus
	FOV (H X V)	7° (H) x 5° (V)	11.0° x 8.2° (WFOV) to 2.2° x 1.6° (NFOV)
	Digital Zoom	2X	2X, 4X
	Focal Length (mm)	100 mm	50x250mm
Video	Sensor	1/2 inch EM-CCD with electron multiplication High sensitivity color / monochrome camera	
	Field of View (D x H x V)	20° 53' x 15° 55' (WIDE) 0° 11' x 0° .08' (TELE)	
	Zoom	Optical: 60X 16.7-1000mm/33-2000mm 60X optical zoom	
	Illumination	Minimum illumination < 200µlux	
Pan & Tilt	Azimuth Control	360° continuous	
	Elevation Control	± 90 °	
	Pan & Tilt Slew Rate	0 seconds to 60 seconds	
	Pointing Accuracy	Pan ± 0.1° / Tilt ± 0.1°	
Power	Power Source	10 - 28 VDC through supplied 110 /220 VAC power supply	
Environmental Characteristics	Operating Temperature	-40° C to 60° C	
	Environmental Sealing	Fully ruggedized/Mil-STD-810E, NEMA 4 and IP68	

UVSS

EV3000 Series Demo

EST. 2000

Eagle Vision Dual Sensors



UVSS

Customers

EST. 2000



U.S ARMY CORPS OF ENGINEERS



EGYPTIAN AIR FORCE



U.S AIR FORCE



INDIAN AIR FORCE



U.S COAST GUARD



CANADIAN ROYAL POLICE



U.S CENTRAL COMMAND



BROWNSVILLE TX PORT



NASA



MEXICAN NAVY



NANTUCKET MA PORT



FINNISH NAVY



SAUDI ARAMCO OIL



EGYPTIAN NAVY



PEMEX OIL



EST. 2000

Contact Us

Office:

**10 Center Street #401, 402
Chicopee MA, 01013**

Telephone Inquiry/Sales:

**+1 (413) 592-8477 US & Canada
+1 (413) 591-8477 International**

Email:

info@ev3000.com

www.ev3000.com



© United Vision Security Systems - All content protected

United Vision Security Systems

A world without darkness...